


# Diffuser Specialist

S80 Smooth/Smooth

VANTEX™  
AN ALP BRAND



Pattern	Polymer	LT%	Thickness
S80 Smooth/Smooth			
S80 AC	Acrylic Clear	93%	.080 .125 .177 .220
S80 AC 118	Acrylic Clear	94%	.118
S80 AW	Acrylic White	60%	.080 .118
S80 HC	HID Acrylic Clear	93%	.118
S80 PC	Polycarbonate Clear	93%	.118 .177

## Description

S80 flat sheet products are versatile enough to be used as a lighting fixture enclosure or luminous ceiling diffuser. They ensure evenly illuminated lighting enclosures, reducing shadows and reflected glare.

**Acrylic-** most common in lighting applications

**Polycarbonate-** Break resistant used mostly in high vandal and high heat areas.

## Ordering Information

Please call 1.800.880.5483 for price and delivery. Specify dimensions when placing an order.

## Notice

Diffuser Specialist assumes no responsibility for suitability of luminaires and applications. The use of acrylic lenses near and above 80°C temperatures with high UV output light sources will cause degradation of the material. Tolerance for Light Transmission is  $\pm 3\%$ . Subject to changes without notice.

## Ready - To - Go

S80AC080-5050  
S80 Window clear  
Acrylic  
Smooth/ Smooth  
.080 Thickness  
50" X 50"  
Cut to size available

S80AC118-5050  
S80 Window Clear  
Acrylic  
Smooth /Smooth  
.118 Thickness  
50" X 50"  
Cut to size available

S80AC118-4896  
S80 Window Clear  
Acrylic  
Smooth / Smooth  
.118 THICKNESS  
48" X 96"  
Cut to size available

S80AW118-4896  
S80 White #2447  
Acrylic  
Smooth / Smooth  
.118 Thickness  
48" X 96"  
Cut to size available

S80PC118-5050  
S80 window Clear  
Polycarbonate  
Smooth / Smooth  
.118 thickness  
50" x 50"  
Cut to size available

