## **Diffuser Specialist**

VAPOR TIGHT ENCLOSURES, REPLACEMENT LENS & ACCESSORIES A.L.P. BRAND





## TMW Series 4' & 8' Fluorescent Strip Type, 2' Sentry Fluorescent Strip Type

#### Description

The TMW series is A.L.P.'s rugged industrial gasketed enclosure. The strip type housing augments the flexibility of the strip luminaire within with the protection of an enclosed and gasketed enclosure. The TMW housing is sealed against dust and moisture and available in avariety of lens, latch, wire-entry, and lamp configurations.

#### **Applications**

Ideal for use in dusty, dirty, or wet environments including food processing, coldstorage, kitchens, parking garage, carwashes, covered canopies, pedestrian tunnels, concourses, and industrial.

### Certifications

- UL/cUL recognized component
- Wet Location listed
- IP65 (Standard 6-latch configuration)
- NSF International certified for NSF/ ANSI Standard 2—Food Equipment

## **Features**

- Rigid one piece housingconstruction.
- Standard 6-latch for 4' and 10 latch for 8' (IP65).
- En-seal™ gasketing provides superior resistance to moisture absorption versus conventional gaskets
- Standard suitcase style latches.
- Molded latch pockets compatible with standard and tamper-proof latches in Celcon, stainless steel, and polycarbonate.
- Internal metal striplight housing mounts to two #8-32 internal brass studs molded into housing.

#### Housing

 $Compression \ molded \ self-extinguishing \ fiberglass \ reinforced \ polyester \ compound \ with ULHB flame \ rating. \ F1 we ather ability \ rating.$ 

## Gasketing

En-Seal ™ continuous perimeter poured gasket assures lens seal to housing.

#### **Electrical Chassis**

Available internal strip light housing components constructed of 83% reflective, 22-gauge, pre-painted steel.

## **Conduit Entry**

Standard housings available with one 7/8" conduitentry point on either or both ends.

#### l ens

Inline thermal-formed lenses availablein shallow and deep profiles of crepe patterns of acrylic, or polycarbonate.

#### Mounting

Standard stainless steel mounting brackets (BRKTT22PK) clip to housing for surface or all-thread pendant mounting

VT240D 4' VAPOR-TITE SET 4' housing, acrylic crepe lens

7-3/8 X 49-11/16 X 3"

(2) plugs,(6) latch's,

VT296
8' VAPOR-TITE SET
8' housing,
acrylic crepe lens,

7-3/8 X 97-3/4 X 3 (2) plugs, (10) latch's

VT220 2' VAPOR-TITE SET

HOUSING,
ACRYLIC CREPE LENS,

6-3/8 X 25-11/16 X 2

PLUGS(2) LATCH'S (4)

**ALP-Sentry** 

# Diffuser Specialist

VAPOR TIGHT ENCLOSURES, REPLACEMENT LENS & ACCESSORIES A.L.P. BRAND

